



TECHNICAL DATA BULLETIN

6315 Monolec[®] Way Lubricant

LEADERS IN LUBRICANTS

Description:

High quality lubricant for machine ways and other sliding surfaces. Excellent lubricity and good adhesive properties. Very stable for long term use. Contains Monolec[®], LE's exclusive wear-reducing additive. Approved for Cincinnati Machine P-50 specification. USDA H2 rated.

Physical Characteristics – Typical:

ISO Grade	220
Gravity, °API	28.2
Viscosity	
SUS @ 100°F	1192
SUS @ 210°F	102
cSt @ 40°C	226
cSt @ 100°C	20.2
Viscosity Index	95
Flash Point, °F (°C)	440 (227)
Pour Point, °F (°C)	0 (-18)

Application:

Machine tool ways and other sliding surfaces. Excellent for centralized lubrication systems.

Beneficial Qualities:

Special lubricity additives for heavy-duty service.

Written approval for Cincinnati Machine P-50.

USDA H2 rated.

Adhesive properties hold oil to surfaces.

High film strength.

Contains Monolec[®].

Superior performance in the Cincinnati Machine Thermal Stability Test.

LI50075
10/07

LUBRICATION ENGINEERS, Inc.

300 Bailey Ave Fort Worth, Texas 76107
817-916-3200 · 800-537-7683 · fax 817-820-1512
www.LElubricants.com

**LE OPERATES UNDER AN ISO 9001
CERTIFIED QUALITY SYSTEM**